



JD 2600A/ JD 2600B(D 903)

AUTO LENSMETER



7"LCD
JD 2600A



5.6"LCD
JD 2600B(D 903)



Sensitive LCD touch display screen

Just touch the screen can finish your measurement, your operation could be easier and more convenient.

Adjustable LCD display screen

Tilting color screen provides you with clear view from any position such as sitting and standing.



Automatic recognition of single and progressive lens




Hi-speed UV measurement:

Just holding the lens through the sensor, the display will easily indicate the UV measurement by the progress bar.



Measurement screen



Progressive measurement

Automatic measurement of progressive lenses. A graph helps the operator to improve accuracy and speed in the measurement of near and far vision.




Built-in thermal printer

Quick data print with built-in printer. Easy to reload printing paper.



Place for UV test



Specifications:

Range of measurement	
Sphere	0~±25D 0.01/0.12/0.25D steps
Cylinder	0~±9.99D 0.01/0.12/0.25D steps
Axis	0~180° (1° step)
ADD	0~+9.99D 0.01/0.12/0.25D steps
Prism degree	0~15△ 0.01/0.12/0.25△ steps
Measurement mode	
Cylinder	+, +/-, -
Prism	X-Y, P-B
Contact Lens	Soft/hard
Measuring Mode	Single/progressive/automatic recognition

Specifications	
Diameter of lens	Ø20~108mm
PD	45~90mm, 0.5mm steps
Speed	0.1S
Display	TFT LCD JD 2600A(7") JD 2600B(5.6")
Printer	Thermal printer
Dimension	222(D)*161(W)*372(H)mm
Package	515(H)*320(W)*390(D)mm
Weight	~5KG
Power supply	100~240V 50~60Hz

Standard Case: Carrying Aluminum Case

